



KLİMA



VEHICLE AIR CONDITIONING SYSTEMS

KLİMA - VEHICLE AIR CONDITIONING

KC2025001189



KÜHLEISTUNG (AUSSSENTEMPERATUR +35 °C) COOLING CAPACITY (AMBIENT TEMP.+35°C)	6.500 kcal/h (7558 Watt)
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	-
KÜHLMITTEL / REFRIGERANT	R134a
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	COND. (1230 x 800 x 160) mm EVAP., (820x350x165) mm
GEWICHT / WEIGHT	46,7 kg
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	1200 m³ /h
FRISCHLUFTZUFUHR / FRESH AIR	-
STROMVERSÖRGUNG / POWER CONSUMPTION	12 V DC 55 A

KC2025001190



KÜHLEISTUNG (AUSSSENTEMPERATUR +35 °C) COOLING CAPACITY (AMBIENT TEMP.+35°C)	6500 kcal/h (7558 Watt)
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	-
KÜHLMITTEL / REFRIGERANT	R134a
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	COND. (1230 x 800 x 160) mm EVAP., (1090 x 350 x 200) mm
GEWICHT / WEIGHT	46,7 kg
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	1200 m³ /h
FRISCHLUFTZUFUHR / FRESH AIR	-
STROMVERSÖRGUNG / POWER CONSUMPTION	12 V DC 55 A

KC2025001191



KÜHLEISTUNG (AUSSSENTEMPERATUR +35 °C) COOLING CAPACITY (AMBIENT TEMP.+35°C)	9.000 kcal/h (10500 Watt)
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	12.040 kcal/h / (14.000 Watt)
KÜHLMITTEL / REFRIGERANT	R134a
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	1800 x 1350 x 190 mm
GEWICHT / WEIGHT	62,2 kg
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	2040 m³ /h
FRISCHLUFTZUFUHR / FRESH AIR	%25
STROMVERSÖRGUNG / POWER CONSUMPTION	12 V DC 47 A 24 V DC 33 A

KC2025001192



KÜHLEISTUNG (AUSSSENTEMPERATUR +35 °C) COOLING CAPACITY (AMBIENT TEMP.+35°C)	12.000 kcal/h (14.000 Watt)
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	12900 kcal/h (15.000 Watt)
KÜHLMITTEL / REFRIGERANT	R134a
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	1625 x 2510 x 255 mm
GEWICHT / WEIGHT	90 kg
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	4.150 m³ /h
FRISCHLUFTZUFUHR / FRESH AIR	%15
STROMVERSÖRGUNG / POWER CONSUMPTION	12 V DC 74 A 24 V DC 45 A

KLİMA - VEHICLE AIR CONDITIONING

KC2025001193



KÜHLEISTUNG (AUSSENTEMPERATUR +35 °C COOLING CAPACITY (AMBIENT TEMP.+35°C)	18.060 kcal/h (21.000 Watt)	
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	-	
KÜHLMITTEL / REFRIGERANT	R134a	
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	2150 x 2050 x 425 mm	
GEWICHT / WEIGHT	178 kg	
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	4.150 m³ /h	
FRISCHLUFTZUFUHR / FRESH AIR	%100	
STROMVERSORGUNG / POWER CONSUMPTION	380-420V AC/3PH/50Hz 26 V	26 A 58 A

KC2025001194



KÜHLEISTUNG (AUSSENTEMPERATUR +35 °C COOLING CAPACITY (AMBIENT TEMP.+35°C)	21.000 kcal/h (24.400 Watt)	
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	23.500 kcal/h (27.150 Watt)	
KÜHLMITTEL / REFRIGERANT	R134a	
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	2120 x 2050 x 180 mm	
GEWICHT / WEIGHT	135 kg	
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	4.150 m³ /h	
FRISCHLUFTZUFUHR / FRESH AIR	%100	
STROMVERSORGUNG / POWER CONSUMPTION	24 V DC	42,5 A

KC2025001195



KÜHLEISTUNG (AUSSENTEMPERATUR +35 °C COOLING CAPACITY (AMBIENT TEMP.+35°C)	32.680 kcal/h (38.000 Watt)	
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	34.500 kcal/h (40.100 Watt)	
KÜHLMITTEL / REFRIGERANT	R134a	
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	2650 x 2050 x 180 mm	
GEWICHT / WEIGHT	150 kg	
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	6.300 m³ /h	
FRISCHLUFTZUFUHR / FRESH AIR	%100	
STROMVERSORGUNG / POWER CONSUMPTION	24 V DC	86 A

KC2025001196



KÜHLEISTUNG (AUSSENTEMPERATUR +35 °C COOLING CAPACITY (AMBIENT TEMP.+35°C)	36.100 kcal/ h (42.000 Watt)	
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	42500 kcal / h (49500 Watt)	
KÜHLMITTEL / REFRIGERANT	R134a	
ANLAGENGROSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	3100 x 2065 x 240	
GEWICHT / WEIGHT	190 kg / 197 kg	
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	8400 m³/ h	
FRISCHLUFTZUFUHR / FRESH AIR (OPTIONAL)	%70	
STROMVERSORGUNG / POWER CONSUMPTION	24 V DC	105 A

KLİMA - VEHICLE AIR CONDITIONING

KC2025001197



KÜHLEISTUNG (AUSSENTEMPERATUR +35 °C COOLING CAPACITY (AMBIENT TEMP.+35°C)	37.840 kcal/h (44.000 Watt)	
HEIZLEISTUNG (OPTIONAL) HEATING CAPACITY (OPTIONAL)	43.400 kcal/h (50.500 Watt)	
KÜHLMITTEL / REFRIGERANT	R134a	
ANLAGENGRÖSSE (ABMESSUNG L x B x H mm) UNIT SIZE (WIDTH x LENGHT x HEIGHT)	3100 x 2050 x 260 mm	
GEWICHT / WEIGHT	220 kg	
LUFTSTRÖMUNGSLEISTUNG / AIR FLOW	8.000 m³ /h	
FRISCHLUFTZUFUHR / FRESH AIR	%100	
STROMVERSORGUNG / POWER CONSUMPTION	24 V DC	130 A